

cfdocumentsection

Description

Category

Other

Implemented

Usage Syntax

```
[marginbottom="number"]  
[marginleft="number"]  
[marginright="number"]  
[margintop="number"]  
[src="String"]  
[srcfile="String"]  
[mimetype="String"]  
[name="String"]  
[authUser="String"]  
[authPassword="String"]  
[userAgent="String"]  
/>
```

[] = *Optional attribute*

Attributes

Contents

- [cfdocumentsection](#)
- [Description](#)
- [Category](#)
- [Implemented](#)
- [Usage Syntax](#)
- [Attributes](#)
- [Example Usage](#)

Name	Type	Required	Default	Description
marginbottom	number	No		
marginleft	number	No		
marginright	number	No		
margin-top	number	No		
src	String	No		define a url or or a relative path on the local system to a file that should be transfered to a pdf
srcfile	String	No		define a absolute path to a file that should be transfered to a pdf
mimetype	String	No		mimetype of the source (when attribute src or srcfile are defined)
name	String	No		Bookmark name for the section
authUser	String	No		User name sent to the target URL for Basic Authentication. Combined with password to form a base64 encoded string that is passed in the Authenticate header. Does not provide support for Integrated Windows, NTLM, or Kerebos authentication.
authPassword	String	No		Password sent to the target URL for Basic Authentication. Combined with username to form a base64 encoded string that is passed in the Authenticate header. Does not provide support for Integrated Windows, NTLM, or Kerebos authentication.
userAgent	String	No		Text to put in the HTTP User-Agent request header field. Used to identify the request client software.

Example Usage