

cfile

Description

Handles all interactions with files. The attributes you use with cfile depend on the value of the action attribute. For example, if the action = "write", use the attributes associated with writing a text file.

Category

Other

Implemented

Usage Syntax

```
[acl="String"]
action="String"
[serverpassword="String"]
[source="String"]
[attributes="String"]
[destination="String"]
[mode="String"]
[filefield="String"]
[charset="String"]
[nameconflict="String"]
[accept="String"]
[file="String"]
[variable="String"]
[output="Any"]
[addNewLine="Boolean"]
[fixnewline="Boolean"]
[result="String"]
/>
```

[] = *Optional attribute*

Attributes

Contents

- [cfile](#)
- [Description](#)
- [Category](#)
- [Implemented](#)
- [Usage Syntax](#)
- [Attributes](#)
- [Example Usage](#)

Name	Type	Required	Default	Description
acl	String	No		only used for S3 Resources
action	String	Yes		Type of file manipulation that the tag performs.
serverpassword	String	No		allow you to access filesystem, also when access is denied for your context
source	String	No		Absolute pathname of file on web server. On Windows, use backward slashes; on UNIX, use forward slashes.
attributes	String	No		One attribute (Windows) or a comma-delimited list of attributes (other platforms) to set on the file. If omitted, the file's attributes are maintained.
destination	String	No		Absolute pathname of directory or file on web server.
mode	String	No		Applies only to Solaris and HP-UX. Permissions. Octal values of UNIX chmod command. Assigned to owner, group, and other, respectively.
filefield	String	No		Name of form field used to select the file.
charset	String	No		Character set name for the file contents.
nameconflict	String	No		Action to take if filename is the same as that of a file in the directory.
accept	String	No		Limits the MIME types to accept. Comma-delimited list. For example, to permit JPG and Microsoft Word file uploads: accept = "image/jpg, application/msword" The browser uses file extension to determine file type.
file	String	No		Absolute pathname of file on web server.
variable	String	No		Name of variable to contain contents of text file.
output	Any	No		Content of the file to be created.
addNewLine	Boolean	No		Yes: appends newline character to text written to file
fixnewline	Boolean	No		
result	String	No		Name of the result value (default:cffile)

Example Usage