

# cform

## Description

Builds a form with CFML custom control tags that provide more functionality than standard HTML form input elements.

## Category

Other

## Implemented

## Usage Syntax

```
[name="String"]
[action="String"]
[preserveData="Boolean"]
[enableCAB="Boolean"]
[target="String"]
[method="String"]
[encType="String"]
[passThrough="Any"]
[codeBase="String"]
[archive="String"]
[scriptSrc="String"]
[id="String"]
[onReset="String"]
[onLoad="String"]
[onSubmit="String"]
[style="String"]
[class="String"]
[format="String"]
[skin="String"]
[width="String"]
[height="String"]
[preloader="Boolean"]
[timeout="number"]
[wMode="String"]
[accessible="Boolean"]
```

## Contents

- [cform](#)
- [Description](#)
- [Category](#)
- [Implemented](#)
- [Usage Syntax](#)
- [Attributes](#)
- [Example Usage](#)

```
[accept="String"]
[acceptcharset="String"]
[title="String"]
[dir="String"]
[lang="String"]
[onclick="String"]
[ondblclick="String"]
[onmousedown="String"]
[onmouseup="String"]
[onmouseover="String"]
[onmousemove="String"]
[onmouseout="String"]
[onkeypress="String"]
[onkeyup="String"]
[onkeydown="String"]
/>
```

[] = *Optional attribute*

## Attributes

Name	Type	Required	Default	Description
name	String	No		A name for the form you are creating.
action	String	No		The name of the ColdFusion page that executed when the form is submitted for processing.
preserveData	Boolean	No		Optional. "Yes" or "No." Specifies whether to display the data that was entered into cfform controls in the action page. "Yes" resets the value of the control to the value submitted when the form is submitted to itself. This works as expected for the cftextinput and cfslider controls. This attribute can be used only if the form and action are on a single page, or if the action page has a form that contains controls with the same names as the corresponding controls on the form page.
enableCAB	Boolean	No		This attribute has been deprecated and is non-functional.
target	String	No		The name of the window or window frame to which the form output is sent.
method	String	No		other than post will ignored

encType	String	No	<p>The MIME type used to encode data sent by the POST method. The default value is application/x-www-form-urlencoded. It is recommended that you accept the default value. This attribute is included for compatibility with the HTML form tag.</p>
passThrough	Any	No	<p>Used for HTML attributes that are not explicitly supported by cform. If you specify an attribute and value, they are passed to the HTML code that is generated for the cinput tag.</p>
codeBase	String	No	<p>URL for a downloadable JRE plugin (for Internet explorer only). Default is /CFIDE/classes/cf-j2re-win.cab.</p>
archive	String	No	<p>URL for a downloadable Java classes for ColdFusion controls. Default is /CFIDE/classes/CFJava2.jar.</p>
scriptSrc	String	No	
id	String	No	
onReset	String	No	
onLoad	String	No	
onSubmit	String	No	<p>JavaScript function to execute after other input validation returns. Use this attribute to execute JavaScript for preprocessing data before the form is submitted</p>
style	String	No	
class	String	No	
format	String	No	
skin	String	No	
width	String	No	
height	String	No	
preloader	Boolean	No	
timeout	number	No	
wMode	String	No	
accessible	Boolean	No	
accept	String	No	
acceptcharset	String	No	
title	String	No	
dir	String	No	

lang	String	No
onclick	String	No
ondblclick	String	No
onmousedown	String	No
onmouseup	String	No
onmouseover	String	No
onmousemove	String	No
onmouseout	String	No
onkeypress	String	No
onkeyup	String	No
onkeydown	String	No

## Example Usage