

cftp

Description

Lets users implement File Transfer Protocol (FTP) operations.

Category

Other

Implemented

Usage Syntax

```
action="String"  
[username="String"]  
[password="String"]  
[server="String"]  
[timeout="number"]  
[port="number"]  
[connection="String"]  
[proxyServer="String"]  
[proxyPort="number"]  
[proxyUser="String"]  
[proxyPassword="String"]  
[retrycount="number"]  
[stoponerror="Boolean"]  
[passive="Boolean"]  
[name="String"]  
[directory="String"]  
[ASCIIExtensionList="String"]  
[transferMode="String"]  
[remoteFile="String"]  
[localFile="String"]  
[failIfExists="Boolean"]  
[existing="String"]  
[new="String"]  
[item="String"]  
[result="String"]  
/>
```

Contents

- [cftp](#)
- [Description](#)
- [Category](#)
- [Implemented](#)
- [Usage Syntax](#)
- [Attributes](#)
- [Example Usage](#)

[] = *Optional attribute*

Attributes

Name	Type	Required	Default	Description
action	String	Yes		the action that should be execute
username	String	No		The Username for the connection
password	String	No		The Password for the connection
server	String	No		The Server to connect
timeout	number	No		timeout for the connection
port	number	No		server port of the connection
connection	String	No		the name for the connection, used to cache the connection
proxyServer	String	No		Host name or IP address of a proxy server. The port number on the proxy server from which the object is requested. Default is 80.
proxyPort	number	No		When used with resolveURL, the URLs of retrieved documents that specify a port number are automatically resolved to preserve links in the retrieved document.
proxyUser	String	No		When required by a proxy server, a valid username.
proxyPassword	String	No		When required by a proxy server, a valid password.
retrycount	number	No		retry count
stoponerror	Boolean	No		define if execution halt on error or not
passive	Boolean	No		enable passive mode
name	String	No		name of the query for list directory
directory	String	No		remote directory to list
ASCIIExtensionList	String	No		Delimited list of file extensions that force ASCII transfer mode, if transferMode = "auto".
transferMode	String	No		ascii, binary or auto mode
remoteFile	String	No		File on the Server
localFile	String	No		File on the current machine

<code>failIfExists</code>	Boolean	No	throw a error if local file already exist or overwrite it
<code>existing</code>	String	No	source or existing file or directory to rename
<code>new</code>	String	No	new name for file or directory
<code>item</code>	String	No	item on the server
<code>result</code>	String	No	Name of the result value (default:cfftp)

Example Usage