

cfimap

Description

Retrieves and deletes e-mail messages from a Imap mail server.

Category

Other

Implemented

Usage Syntax

```
server="String"  
[uid="String"]  
[port="number"]  
[username="String"]  
[password="String"]  
[action="String"]  
[name="String"]  
[messageNumber="String"]  
[attachmentPath="String"]  
[timeout="number"]  
[maxRows="number"]  
[startRow="number"]  
[generateUniqueFileNames="Boolean"]  
/>
```

[] = Optional attribute

Attributes

Contents

- [cfimap](#)
- [Description](#)
- [Category](#)
- [Implemented](#)
- [Usage Syntax](#)
- [Attributes](#)
- [Example Usage](#)

Name	Type	Required	Default	Description
server	String	Yes		Host name biff.upperlip.com or IP address 192.1.2.225 of the Imap server.
uid	String	No		
port	number	No		Defaults to the standard Imap port, 143.
username	String	No		If no user name is specified, the Imap connection is anonymous.
password	String	No		Password that corresponds to user name.
action	String	No		Specifies the mail action.
name	String	No		Name for the index query.
messageNumber	String	No		Can be a comma-separated list of the message ids
attachmentPath	String	No		Allows attachments to be written to the specified directory when action = "getAll". If an invalid attachmentPath is specified, no attachment files are written to the server.
timeout	number	No		Specifies the maximum time, in seconds, to wait for mail processing. Defaults is 60 seconds.
maxRows	number	No		Sets the number of messages returned, starting with the number in the startRow attribute. This attribute is ignored if messageNumber is specified.
startRow	number	No		Specifies the first row number to be retrieved. Default is 1. This attribute is ignored if messageNumber is specified.
generateUniqueFilenames	Boolean	No		Boolean indicating whether to generate unique filenames for the files attached to an e-mail message to avoid naming conflicts when the files are saved. Default is NO.

Example Usage