

cfinsert

Description

Inserts records in data sources.

Category

Other

Implemented

Usage Syntax

```
dataSource="String"  
tableName="String"  
[tableOwner="String"]  
[tableQualifier="String"]  
[username="String"]  
[password="String"]  
[formFields="String"]  
/>
```

[] = Optional attribute

Attributes

Contents

- [cfinsert](#)
- [Description](#)
- [Category](#)
- [Implemented](#)
- [Usage Syntax](#)
- [Attributes](#)
- [Example Usage](#)

Name	Type	Required	Default	Description
dataSource	String	Yes		Name of the data source that contains your table.
tableName	String	Yes		Name of the table you want the form fields inserted in.
tableOwner	String	No		For data sources that support table ownership such as SQL Server, Oracle, and Sybase SQL Anywhere, use this field to specify the owner of the table. For data sources that support table qualifiers, use this field to specify the qualifier for the table. The purpose of table qualifiers varies across drivers. For SQL Server and Oracle, the qualifier refers to the name of the database that contains the table. For the Intersolv dBase driver, the qualifier refers to the directory where the DBF files are located.
tableQualifier	String	No		
username	String	No		If specified, username overrides the username value specified in the ODBC setup.
password	String	No		If specified, password overrides the password value specified in the ODBC setup.
formFields	String	No		A comma-separated list of form fields to insert. If this attribute is not specified, all fields in the form are included in the operation.

Example Usage