

# cflog

## Description

Writes a message to a log file.

## Category

Other

## Implemented

## Usage Syntax

```
text="String"  
[charset="String"]  
[log="String"]  
[file="String"]  
[type="String"]  
[thread="String"]  
[date="datetime"]  
[time="String"]  
[application="Boolean"]  
/>
```

*[] = Optional attribute*

## Attributes

## Contents

- [cflog](#)
- [Description](#)
- [Category](#)
- [Implemented](#)
- [Usage Syntax](#)
- [Attributes](#)
- [Example Usage](#)

<b>Name</b>	<b>Type</b>	<b>Required</b>	<b>Default</b>	<b>Description</b>
text	String	Yes		The message text to log.
charset	String	No		
log	String	No		If you omit the file attribute, specifies the standard log file in which to write the message. Ignored if you specify a file attribute
file	String	No		
type	String	No		The type or severity of the message.
thread	String	No		Specifies whether to log the thread ID. The thread ID identifies which internal service thread logged a message. Since a service thread normally services a CFML page request to completion, then moves on to the next queued request, the thread ID serves as a rough indication of which request logged a message. Leaving thread IDs turned on can help diagnose patterns of server activity.
date	datetime	No		Specifies whether to log the system date.
time	String	No		Specifies whether to log the system time.
application	Boolean	No		Specifies whether to log the application name if one has been specified in a cfapplication tag.

## Example Usage