

cfmailparam

Description

Sets a header or attach a file to an e-mail.

Category

Other

Implemented

Usage Syntax

```
[file="String"]  
[name="String"]  
[value="String"]  
[type="String"]  
[disposition="String"]  
[contentid="String"]  
/>
```

[] = Optional attribute

Attributes

Contents

- [cfmailparam](#)
- [Description](#)
- [Category](#)
- [Implemented](#)
- [Usage Syntax](#)
- [Attributes](#)
- [Example Usage](#)

Name	Type	Required	Default	Description
file	String	No		Attaches the specified file to the message. This attribute is mutually exclusive with the name attribute.
name	String	No		Specifies the name of the header. Header names are case insensitive. This attribute is mutually exclusive with the file attribute.
value	String	No		Indicates the value of the header.
type	String	No		The MIME media type of the part.
disposition	String	No		How the attached file is to be handled. Can be one of the following: attachment: presents the file as an attachment. inline: displays the file contents in the message.
contentid	String	No		The Identifier for the attached file. This ID should be globally unique and is used to identify the file in an IMG or other tag in the mail body that references the file content.

Example Usage

```
<--- Adding some headers: --->
from="sender@host"
to="recipient@host"
subject="Urgent, please read!"
type="html"
>
  name="MIME-Version" value="1.0" />
  name="X-Priority" value="1" />
  name="X-MSMail-Priority" value="High" />
  name="Reply-To" value="reply@host" />
```

This message adds 4 headers by using cfmailparam tags.

```
<--- Adding an attachment: --->
from="sender@host"
to="recipient@host"
subject="An attachment for you"
type="html"
>
  file="#expandPath('images/logo.gif')#" type="image/gif" />
```

This message adds an attachment by using a cfmailparam.

