

## Contents

- [cfchartseries](#)
- [Syntax](#)
- [Description](#)
- [Body](#)
- [Attributes](#)

Return to [Tags](#) or [Functions](#)

# cfchartseries

## Syntax

```
[colorlist="string"]  
[datalabelstyle="string"]  
[itemcolumn="string"]  
[markerstyle="string"]  
[paintstyle="string"]  
[query="any"]  
[seriescolor="string"]  
[serieslabel="string"]  
type="string"  
[valuecolumn="string"]>  
[]
```

*[] = Optional attribute*

## Description

Used with the cfchart and cfchartseries tags. This tag defines chart data points. Its data is submitted to the cfchartseries tag.

## Body

This tag may have a body.

## Attributes

The attributes for this tag are fixed. Except for the following attributes no other attributes are allowed.

Name	Type	Required	Description
			Applies if chartseries type attribute = "pie". Sets pie slice colors.
colorlist	string	No	Comma-delimited list of hex values or supported, named web colors; see name list in the cfchart Usage section. For a hex value, use the form "###xxxxxx", where x = 0-9 or A-F; use two pound signs or none.
			Specifies the way in which the color is applied to the item in the series: <ul style="list-style-type: none"> <li>- None = nothing is printed (default)</li> <li>- Value = the value of the datapoint</li> <li>- Rowlabel = the row's label</li> <li>- Columnlabel = the column's label</li> <li>- Pattern</li> </ul>
datalabelstyle	string	No	
itemcolumn	string	No	Name of a column in the query specified in the query attribute; contains the item label for a data point to graph.
markerstyle	string	No	Applies to chartseries type attribute values line, curve and scatter, and show3D attribute value no.
paintstyle	string	No	Sets the paint display style of the data series.
query	any	No	Name of CFML query from which to get data.
			Color of the main element (such as the bars) of a chart. For a pie chart, the color of the first slice.
seriescolor	string	No	Hex value or supported named color; see name list in the cfchart Usage section. For a hex value, use the form "###xxxxxx", where x = 0-9 or A-F; use two pound signs or none.
serieslabel	string	No	Text of data series label
type	string	Yes	Sets the chart display style
valuecolumn	string	No	Name of a column in the query specified in the query attribute; contains data values to graph.

 Categories:

- [TAG](#)