

Contents

- [cfcontent](#)
- [Syntax](#)
- [Description](#)
- [Body](#)
- [Attributes](#)

Return to [Tags](#) or [Functions](#)

cfcontent

Syntax

```
[content="binary"]  
[deletefile="boolean"]  
[file="string"]  
[range="boolean"]  
[reset="boolean"]  
[type="string"]  
[variable="any"] >  
[]
```

This tag is also supported within cfscrip.

```
content  
[content="binary"]  
[deletefile="boolean"]  
[file="string"]  
[range="boolean"]  
[reset="boolean"]  
[type="string"]  
[variable="any"] {  
}
```

[] = Optional attribute

Description

Defines the MIME type returned by the current page. Optionally, lets you specify the name of a file to be returned with the page.

Body

This tag may have a body.

Attributes

The attributes for this tag are fixed. Except for the following attributes no other attributes are allowed.

Name	Type	Required	Description
content	binary	No	This Attribute is deprecated Yes or No. Yes deletes the file after the download operation. Defaults to No.
deletefile	boolean	No	This attribute applies only if you specify a file with the file attribute.
file	string	No	The name of the file being retrieved
range	boolean	No	Yes or No. Yes allows download ranges, no forbids download range, default let it open for client.
reset	boolean	No	Yes or No. Yes discards output that precedes the call to cfcontent. No preserves the output that precedes the call. Defaults to Yes. The reset and file attributes are mutually exclusive. If you specify a file, the reset attribute has no effect.
type	string	No	Defines the File/ MIME content type returned by the current page.
variable	any	No	the variable name to the content to output as binary

 Categories:

- [TAG](#)