

## Contents

- [cftp](#)
- [Syntax](#)
- [Description](#)
- [Body](#)
- [Attributes](#)

Return to [Tags](#) or [Functions](#)

# cftp

## Syntax

```
action="string"  
[asciiextensionlist="string"]  
[connection="string"]  
[directory="string"]  
[existing="string"]  
[failifexists="boolean"]  
[item="string"]  
[localfile="string"]  
[name="string"]  
[new="string"]  
[passive="boolean"]  
[password="string"]  
[port="number"]  
[proxypassword="string"]  
[proxyport="number"]  
[proxyserver="string"]  
[proxyuser="string"]  
[remotefile="string"]  
[result="string"]  
[retrycount="number"]  
[server="string"]  
[stoponerror="boolean"]  
[timeout="number"]  
[transfermode="string"]  
[username="string"]>
```

This tag is also supported within cfscript.

```
ftp
action="string"
[asciiextensionlist="string"]
[connection="string"]
[directory="string"]
[existing="string"]
[failifexists="boolean"]
[item="string"]
[localfile="string"]
[name="string"]
[new="string"]
[passive="boolean"]
[password="string"]
[port="number"]
[proxypassword="string"]
[proxyport="number"]
[proxyserver="string"]
[proxyuser="string"]
[remotefile="string"]
[result="string"]
[retrycount="number"]
[server="string"]
[stoponerror="boolean"]
[timeout="number"]
[transfermode="string"]
[username="string"];
```

*[] = Optional attribute*

## Description

Lets users implement File Transfer Protocol (FTP) operations.

## Body

This tag can't have a body.

## Attributes

The attributes for this tag are fixed. Except for the following attributes no other attributes are allowed.

<b>Name</b>	<b>Type</b>	<b>Required</b>	<b>Description</b>
action	string	Yes	the action that should be execute
asciiextensionlist	string	No	Delimited list of file extensions that force ASCII transfer mode, if transferMode = "auto".
connection	string	No	the name for the connection, used to cache the connection
directory	string	No	remote directory to list
existing	string	No	source or existing file or directory to rename
failifexists	boolean	No	throw a error if local file already exist or overwrite it
item	string	No	item on the server
localfile	string	No	File on the current machine
name	string	No	name of the query for list directory
new	string	No	new name for file or directory
passive	boolean	No	enable passive mode
password	string	No	The Password for the connection
port	number	No	server port of the connection
proxypassword	string	No	When required by a proxy server, a valid password.
proxyport	number	No	The port number on the proxy server from which the object is requested. Default is 80. When used with resolveURL, the URLs of retrieved documents that specify a port number are automatically resolved to preserve links in the retrieved document.
proxyserver	string	No	Host name or IP address of a proxy server.
proxyuser	string	No	When required by a proxy server, a valid username.
remotefile	string	No	File on the Server
result	string	No	Name of the result value (default:cfftp)
retrycount	number	No	retry count
server	string	No	The Server to connect
stoponerror	boolean	No	define if execution halt on error or not
timeout	number	No	timeout for the connection
transfermode	string	No	ascii, binary or auto mode
username	string	No	The Username for the connection

 Categories:

- [TAG](#)